



2022.0

FESD Web Services

Developer guide

Contents

WorkZone Content Server 2022.0 Developer's Guide to FESD Web Services	4
WorkZone links	4
What's new	5
WorkZone Content Server FESD Web Services 2022.0	5
About the FESD Standard for Web Services	7
Record	8
Record Comment	13
Record Reminder	14
Record Document Association	15
Data mapping and WorkZone Content Server FESD Web Services imple- mentation	16
Document	18
Document Comment	19
DocumentVersion	20
Person	22
Person Address	25
Person CareOf	28
Person Role Relation	28
Organization	29
Organization Address	30
Organization Role Relation	30
OrganizationalUnit	31
OrganisationalUnit Address	33
OrganizationalUnit Role Relation	33
Building	34
Building Address	36
Cadastre	37

RealProperty	41
CaseFile	48
CaseFile Comment	53
CaseFile Reminder	54
CaseFile Party	55
CaseFile Object	56
Terms and conditions	58
Intellectual Property Rights	58
Disclaimer	58

WorkZone Content Server 2022.0 Developer's Guide to FESD Web Services

This guide describes the FESD to WorkZone Content Server FESD Web Services data model mapping and WorkZone Content Server FESD Web Services implementation of the FESD standard for web services.

The guide contains descriptions of differences between the FESD standard and its implementation in Open WSI for every FESD parameter.

The target audience of the document is the Danish State Archives, KMD developers, and developers of 3rd party applications that use WorkZone Content Server FESD Web Services OpenWSI.

WorkZone links

- [WorkZone support](#)
- [WorkZone website](#)
- [WorkZone portal](#)

What's new

WorkZone Content Server FESD Web Services 2022.0

No changes in this release.

[WorkZone Content Server FESD Web Services 2021.3](#)

No changes in this release.

[WorkZone Content Server FESD Web Services 2021.2](#)

No changes in this release.

[WorkZone Content Server FESD Web Services 2021.1](#)

No changes in this release.

[WorkZone Content Server FESD Web Services 2020.3](#)

No changes in this release.

[WorkZone Content Server FESD Web Services 2020.2](#)

No changes in this release.

[WorkZone Content Server FESD Web Services 2020.1](#)

No changes in this release.

[WorkZone Content Server FESD Web Services 2020.0](#)

No changes in this release.

[WorkZone Content Server FESD Web Services 2019.3](#)

No changes in this release.

[WorkZone Content Server FESD Web Services 2019.2](#)

No changes in this release.

[WorkZone Content Server FESD Web Services 2019.1](#)

No changes in this release.

[WorkZone Content Server FESD Web Services 2019.0](#)

No changes in this release.

[WorkZone Content Server FESD Web Services 2018.2](#)

No changes in this release.

[WorkZone Content Server FESD Web Services 2018.1](#)

No changes in this release.

[WorkZone Content Server FESD Web Services 2018.0](#)

No changes in this release.

[WorkZone Content Server 2016 R2](#)

No changes in this release.

[WorkZone Content Server 2016](#)

No changes in this release.

[WorkZone Content Server FESD Web Services 2014 R2](#)

No changes in this release.

About the FESD Standard for Web Services

This documentation describes how the OpenWSI component of WorkZone Content Server FESD Web Services implements the FESD standard for web services.

The WorkZone Content Server FESD Web Services data model differs from the FESD data model. In order to ensure compatibility between the two data models, WorkZone Content Server FESD Web Services OpenWSI implements mapping between FESD and WorkZone Content Server FESD Web Services objects, object relations, and object attributes.

Due to gaps in revision 0.1 of the FESD standard and the current WorkZone Content Server FESD Web Services data model and technical implementation, OpenWSI is not fully compatible with the FESD standard.

Record

Mapping of the FESD attributes to the WorkZone Content Server FESD Web Services database fields and notes on WorkZone Content Server FESD Web Services implementation are presented in the table below.

FESD Parameter	WorkZone Content Server FESD Web Services Table	WorkZone Content Server FESD Web Services Field	WorkZone Content Server FESD Web Services Implementation Notes
userIdentifier	N/A	N/A	Is recorded to Use_log.identification field.
caseFileIdentifier	Record	file_key	Parameter type is GUID. Corresponding file_key from File table is found by fesd_id_key equal to this value.
recordIdentifier	Record	fesd_id_key	Parameter type is GUID instead of int(10) specified by FESD standard.
uniqueIdentifier	Record	fesd_id_key	Parameter type is GUID instead of int(10) specified by FESD standard.
year	Record	N/A	Calculated as year part of the Record.created field.
sequenceNumber	Record	record_key	
caseFileReference	Record	file_key	Parameter type is GUID instead of char(10) specified

FESD Parameter	WorkZone Content Server FESD Web Services Table	WorkZone Content Server FESD Web Services Field	WorkZone Content Server FESD Web Services Implementation Notes
----------------	---	---	--

by FESD standard. Used for output: Corresponding **fesd_id_key** from **File** table is found by **file_key**.

caseFileSequenceNumber	Record	record_no	
registrationDate	Record	created	Ignored at input. Is filled in with the date of Record creation.
documentTypeReference	Record	record_grp	Parameter type is char(32) instead of char(2) specified by FESD standard.
documentDate	Record	letter_date	
noDocumentDateIndicator	N/A	N/A	Ignored at input. Is not stored in WorkZone Content Server FESD Web Services database. Calculated for GetRecord method: '1' if Record.letter_date is empty, '0' otherwise
recordStatusCode	Record	record_type	Parameter type is char(32) instead of char(2) specified by FESD standard.

FESD Parameter	WorkZone Content Server FESD Web Services Table	WorkZone Content Server FESD Web Services Field	WorkZone Content Server FESD Web Services Implementation Notes
recordContentsDescriptionText	Record_title	text	
recordContentsDescriptionNonDisclosureIndicator	Record	not_public_desc	Parameter type is unsignedByte instead of char (1) specified by FESD standard. Method accepts only '0' and '1'. '1' in method input and output = 'J' in WorkZone Content Server FESD Web Services database, '0' in method input and output = 'N' in WorkZone Content Server FESD Web Services database.
recordContentsAlternativeDescriptionText	Localized_record_text	text	
recordDeprecationDate	Record	deprecation	
executionDate	Record	execution	
recordDeadline	Record	reply_time_	

FESD Parameter	WorkZone Content Server FESD Web Services Table	WorkZone Content Server FESD Web Services Field	WorkZone Content Server FESD Web Services Implementation Notes
		limit_date	
nonDisclosureDescriptionText	Record	legislation_ref	
nonDisclosureEvaluationDate	Record	evaluation	
recordPaper	Record	medium	Parameter type is unsignedByte instead of char (1) specified by FESD standard. Method accepts only '0' and '1'. '1' in method input and output = 'P' in WorkZone Content Server FESD Web Services database, '0' in method input and output = 'E' in WorkZone Content Server FESD Web Services database.
loanDate	Record_location	received	
borrowerReference	Record_location	recipient	Parameter type is GUID instead of int(10) specified by

FESD Parameter	WorkZone Content Server FESD Web Services Table	WorkZone Content Server FESD Web Services Field	WorkZone Content Server FESD Web Services Implementation Notes
	ation		FESD standard. Algorithms of storing and fetching this parameter to / from WorkZone Content Server FESD Web Services database are similar to algorithms for case-FileResponsibleOfficerReference parameter of CaseFile.
createdByReference	Record	create_user	Parameter type is GUID instead of int(10) specified by FESD standard. Ignored in input. The field Record.create_user in database is filled in with name code of user who called CreateRecord method. For output, it is retrieved as fesd_id_key from a row found in Users table by user_name = value of the field.
lastUpdatedDate	Record		
lastUpdatedByReference	Record		
responsibleOfficerReference / responsibleCaseOfficerReference	Record		

FESD Parameter	WorkZone Content Server FESD Web Services Table WorkZone Content Server FESD Web Services Field WorkZone Content Server FESD Web Services Implementation Notes
sender	Record_name
recipient	Record_name
comment	See Record Comment.
reminder	See Record Reminder.
documentAccosiation	See Record Document Association.

Record Comment

Comments are related to their Records via **record_key** fields in **Record** and **Record_comment** tables.

Mapping of the FESD attributes to the WorkZone Content Server FESD Web Services database fields and notes on WorkZone Content Server FESD Web Services implementation are presented in the table below.

FESD Parameter	WorkZone Content Server FESD Web Services Table	WorkZone Content Server FESD Web Services Field	WorkZone Content Server FESD Web Services Implementation Notes
informationTypeCode	Record_comment	comment_type	Parameter type is char(32) instead of char(2) specified by FESD standard.
cancellationDate	Record_comment	delete_date	
createdOnBehalfOfReference	Record_comment	on_behalf_of	Parameter type is GUID instead of int (10) specified by FESD standard. Algorithms of storing and fetching this parameter to / from WorkZone Content Server FESD Web Services database are similar to algorithms for case-FileResponsibleOfficerReference parameter of CaseFile.
commentText	Record_comment	text	
commentDocumentReference	Record_comment	attach_record_key	Parameter type is GUID instead of int (10) specified by FESD standard.

Record Reminder

Reminders are related to their Records via **record_key** fields in Record and **Record_reminder** tables.

Mapping of the FESD attributes to the WorkZone Content Server FESD Web Services database fields and notes on WorkZone Content Server FESD Web Services implementation are presented in the table below.

FESD Parameter	WorkZone Content Server FESD Web Services Table	WorkZone Content Server FESD Web Services Field	WorkZone Content Server FESD Web Services Implementation Notes
reminderDate	Record_reminder	reminder_date	
reminderTypeCode	Record_reminder	reminder_code	Parameter type is char(3) instead of char(2) specified by FESD standard.
descriptionText	Record_reminder	text	
responsibleReference	Record_reminder	name_code	Parameter type is GUID instead of int(10) specified by FESD standard. Algorithms of storing and fetching this parameter to / from the WorkZone Content Server FESD Web Services database are similar to algorithms for caseFileResponsibleOfficerReference parameter of CaseFile.
N/A	Record_reminder	name_key	Is filled in with name_key of Employee referred by name_code .
N/A	Record_reminder	name_type	Is filled in with 'M' (Employee)

Record Document Association

Records and Documents are associated via Record's **fesd_id_key** and Document's **primary_record_key** fields in **Record** table.

Document association is recorded into the WorkZone Content Server FESD Web Services database automatically by the following algorithm:

1. Find Document in Record table by **fesd_id_key = documentIdentifier**.
2. Check that value in the **primary_record_key** field of the found row is equal to **record_key**.
3. Update **primary_record_key** with **record_key** of the Record.

Data mapping and WorkZone Content Server FESD Web Services implementation

Mapping of the FESD attributes to the WorkZone Content Server FESD Web Services database fields and notes on WorkZone Content Server FESD Web Services implementation are presented in the table below.

FESD Parameter	WorkZone Content Server FESD Web Services Table	WorkZone Content Server FESD Web Services Field	WorkZone Content Server FESD Web Services Implementation Notes
documentIdentifier	Record	fesd_id_key	Parameter type is GUID instead of int(10) specified by FESD standard. This field is used for locating document in Record table by fesd_id_key .
documentAssosiationCode	N/A	N/A	Not implemented by OpenWSI. Ignored at input.
documentAssosiationDate	N/A	N/A	Not implemented by OpenWSI. Ignored at input.

FESD Parameter	WorkZone Content Server FESD Web Services Table	WorkZone Content Server FESD Web Services Field	WorkZone Content Server FESD Web Services Implementation Notes
documentAssosiationCreatorReference	N/A	N/A	Not implemented by OpenWSI. Ignored at input.

Document

Mapping of the FESD attributes to the WorkZone Content Server FESD Web Services database fields and notes on WorkZone Content Server FESD Web Services implementation are presented in the table below.

FESD Parameter	WorkZone Content Server FESD Web Services Table	WorkZone Content Server FESD Web Services Field	WorkZone Content Server FESD Web Services Implementation Notes
userIdentifier	N/A	N/A	Is recorded to the Use_log.identification field.
documentIdentifier	Record	fed_id_key	Parameter type is GUID instead of int(10) specified by FESD standard.
uniqueIdentifier	Record	fed_id_key	Parameter type is GUID instead of int(10) specified by FESD standard.
documentCategoryCode	Record	record_grp	Parameter type is char(32) instead of char(2) specified by FESD standard.
titleText	Record_title	text	
paperIndicator	Record	medium	Parameter type is unsignedByte instead of char(1) specified by FESD standard. Method accepts only '0' and '1'. '1' in method input and output = 'P' in WorkZone Content Server FESD Web Services database, '0' in method input and output =

FESD Parameter	WorkZone Content Server FESD Web Services Table	WorkZone Content Server FESD Web Services Field	WorkZone Content Server FESD Web Services Implementation Notes
			'E' in WorkZone Content Server FESD Web Services database.
paperPlacementDescriptionText	Record	physical_reference	
documentStatusCode	Record	record_type	Parameter type is char(32) instead of char(2) specified by FESD standard.
creatorReference	Record	create_user	Parameter type is GUID instead of int(10) specified by FESD standard. For output, it is retrieved as fesd_id_key from a row found in Users table by user_name = value of the field.
nonDisclosureDescriptionText	Record	legislation_ref	Parameter type is varchar(256) instead of char(16) specified by FESD standard.
comment	See Record Comment.		

Document Comment

Reminders are related to their Records via **record_key** fields in **Record** and **Record_reminder** tables.

Implementation is the same as for Record Comment.

DocumentVersion

The following rules are applied to WorkZone Content Server FESD Web Services’s implementation of the **DocumentVersion** object:

- Only one DocumentVersion may be created for a Document.
- Documents with no versions have NULL value in the field **external_doc_id**.
- **CreateDocumentVersion** method returns ERR_PERMISSION_DENIED if called for a Document with 1 version.

Mapping of the FESD attributes to the WorkZone Content Server FESD Web Services database fields and notes on WorkZone Content Server FESD Web Services implementation are presented in the table below.

FESD Parameter	WorkZone Content Server FESD Web Services Table	WorkZone Content Server FESD Web Services Field	WorkZone Content Server FESD Web Services Implementation Notes
userIdentifier	N/A	N/A	Is recorded to Use_log.identification field.
documentVersionIdentifier	Record	fed_id_key	Parameter type is GUID.
uniqueIdentifier	Record	fed_id_key	Parameter type is GUID instead of int (10) specified by FESD standard.
documentIdentifier	Record	document_version_key	Parameter type is GUID.
documentReference	Record	document_version_key	The same as documentIdentifier . For UpdateDocumentVersion method, should be equal to GUID of Version’s document; otherwise, ERR_NOT_FOUND is returned.

FESD Parameter	WorkZone Content Server FESD Web Services Table	WorkZone Content Server FESD Web Services Field	WorkZone Content Server FESD Web Services Implementation Notes
documentVersionNumber	Record	version_no	
renditionTypeCode	N/A	N/A	Not implemented by OpenWSI.
activeIndicator	N/A	N/A	Not implemented by OpenWSI.
archiveFormatCode	Record	document_type	Parameter type is char(32) instead of char(10) specified by FESD standard.
creatorReference	Record	create_user	Parameter type is GUID instead of int (10) specified by FESD standard. For output, it is retrieved as fesd_id_key from a row found in Users table by user_name = value of the field.
archiveReference	N/A	N/A	Not implemented by OpenWSI. Ignored at input.
documentContents	Record	external_doc_id	Value of field Record.external_doc_id points to the location of document contents in the archive database.

Person

Mapping of the FESD attributes to the WorkZone Content Server FESD Web Services database fields and notes on WorkZone Content Server FESD Web Services implementation are presented in the table below.

FESD Parameter	WorkZone Content Server FESD Web Services Table	WorkZone Content Server FESD Web Services Field	WorkZone Content Server FESD Web Services Implementation Notes
userIdentifier	N/A	N/A	Is recorded to Use_log.identification field.
personIdentifier	Name	fed_id_key	Parameter type is GUID.
uniqueIdentifier	Name	fed_id_key	Parameter type is GUID instead of int(10) specified by FESD standard.
N/A	Name	name_type	Is filled in with 'C' if personCivilRegistrationIdentifier is not NULL; 'P' otherwise.
personCivilRegistrationIdentifier	Name	name_code	For input: Only applicable for CreatePerson method; ignored for UpdatePerson . For output: Empty for persons of type 'P'.
personNameStructure.personGivenName	Name	name1	Concatenation of personGivenName and personMiddleName with the space character between

FESD Parameter	WorkZone Content Server FESD Web Services Table	WorkZone Content Server FESD Web Services Field	WorkZone Content Server FESD Web Services Implementation Notes
----------------	---	---	--

names.

personNameStructure.personMiddleName	Name	name1	Concatenation of personGivenName and personMiddleName with the space character between names.
personNameStructure.personSurnameName	Name	name2	
personNameForAddressingName	Name	addressing_name	
birthDate	Contact_date	date_stamp	Custom_label field in the row is filled in with organization Identifier value.
birthDateUncertaintyIndicator	Name	birthday_uncertainty	'true' in method input and output = 'J' in WorkZone Content Server FESD Web Services database, 'false' in method input and output = 'N' in WorkZone Content Server FESD Web Services database.
personGenderCode	Contact_info	info	First row in subtable contact_info . Custom_label

FESD Parameter	WorkZone Content Server FESD Web Services Table	WorkZone Content Server FESD Web Services Field	WorkZone Content Server FESD Web Services Implementation Notes
----------------	---	---	--

field is filled in with "Køn" (Gender) value. 'female' in method input and output = 'M' in WorkZone Content Server FESD Web Services database, 'male' in method input and output = 'K' in WorkZone Content Server FESD Web Services database, 'unknown' in method input and output = empty value in WorkZone Content Server FESD Web Services database.

personCivilRegistrationIdentifierStatusCode	Contact_ info info	Second row in subtable contact_info . Custom_label is filled in with "Status" value.
nameAddressProtectionIndicator	Name_ is_pro- address tected	'true' in method input and output = 'J' in WorkZone Content Server FESD Web Services database, 'false' in method input and output = 'N' in WorkZone Content Server FESD Web Services database.
nameAddressProtectionEndDate	Name_ pro-	

FESD Parameter	WorkZone Content Server FESD Web Services Table	WorkZone Content Server FESD Web Services Field	WorkZone Content Server FESD Web Services Implementation Notes
	address	tection_end	
maildeliveryAddress	See Person Address.		
careOf	See Person CareOf.		
roleRelation	Currently not supported by OpenWSI.		

Person Address

Addresses are related to persons by **name_key** fields in the Name and **Name_address** tables.

Mapping of the FESD attributes to the WorkZone Content Server FESD Web Services database fields and notes on WorkZone Content Server FESD Web Services implementation are presented in the table below.

FESD Parameter	WorkZone Content Server FESD Web Services Table	WorkZone Content Server FESD Web Services Field	WorkZone Content Server FESD Web Services Implementation Notes
countryIdentificationCode	Name_address	country_code	
municipalityName	N/A	N/A	Not implemented by OpenWSI. Ignored at input.

FESD Parameter	WorkZone Content Server FESD Web Services Table	WorkZone Content Server FESD Web Services Field	WorkZone Content Server FESD Web Services Implementation Notes
streetCode	N/A	N/A	Not implemented by OpenWSI. Ignored at input.
streetBuildingIdentifier	N/A	N/A	Not implemented by OpenWSI. Ignored at input.
districtSubDivisionIdentifier	N/A	N/A	Not implemented by OpenWSI. Ignored at input.
postOfficeBoxIdentifier	N/A	N/A	Not implemented by OpenWSI. Ignored at input.
postCodeIdentifier	N/A	N/A	Not implemented by OpenWSI. Ignored at input.
mailDeliverySublocationIdentifier	N/A	N/A	Not implemented by OpenWSI. Ignored at input.
floorIdentifier	N/A	N/A	Not implemented by OpenWSI. Ignored at input.
suiteIdentifier	N/A	N/A	Not implemented by OpenWSI. Ignored at input.
secondaryAddressLabel	N/A	N/A	Ignored at input. For output concatenation of 6 address lines with spaces between line contents are returned.
N/A	Name_ address	address_type	Is filled in with 'HA' value.
N/A	Name_ address	name_key	Is filled in with value found in Name table by value of Person's GUID.

FESD Parameter	WorkZone Content Server FESD Web Services Table	WorkZone Content Server FESD Web Services Field	WorkZone Content Server FESD Web Services Implementation Notes
postalAddressFirstLineText	Name_ address	address1	On input this is stored in name_address.address1 . On output name_address.address1 is returned.
postalAddressSecondLineText	Name_ address	address1, address2	On input this is concatenated into name_address.address1 . On output name_address.address2 is returned.
postalAddressThirdLineText	Name_ address	address2	On input this is concatenated into name_address.address2 . On output name_address.address3 is returned.
postalAddressFourthLineText	Name_ address	address2, address3	On input concatenated into name_address.address2 . On output an empty string is returned.
postalAddressFifthLineText	Name_ address	address3	On input concatenated into name_address.address3 . On output an empty string is returned.
postalAddressSixthLineText	Name_ address	address3	On input concatenated into name_address.address3 . On output an empty string is returned.

Person CareOf

The Persons are related to each other via **name_key** and **name_ref_key** fields in the **Name_name** table.

Mapping of the FESD attributes to the WorkZone Content Server FESD Web Services database fields and notes on WorkZone Content Server FESD Web Services implementation are presented in the table below.

FESD Parameter	WorkZone Content Server FESD Web Services Table	WorkZone Content Server FESD Web Services Field	WorkZone Content Server FESD Web Services Implementation Notes
N/A	Name_name	name_ref_key	Is filled in with value found in Name table by value of Person's GUID.
N/A	Name_name	role	Is filled in with "CareOf" value.

Person Role Relation

Person Role Relations are currently not supported by OpenWSI.

Organization

Mapping of the FESD attributes to the WorkZone Content Server FESD Web Services database fields and notes on WorkZone Content Server FESD Web Services implementation are presented in the table below.

FESD Parameter	WorkZone Content Server FESD Web Services Table	WorkZone Content Server FESD Web Services Field	WorkZone Content Server FESD Web Services Implementation Notes
userIdentifier	N/A	N/A	Is recorded to Use_log.identification field.
organizationIdentifier	Name	fesd_id_key	Parameter type is GUID.
uniqueIdentifier	Name	fesd_id_key	Parameter type is GUID instead of int(10) specified by FESD standard.
N/A	Name	name_type	Is filled in with 'J' if CVRnumberIdentifier is specified; 'F' otherwise.
advertisementProtectionIndication	Name	advertisement	'true' in method input and output = 'J' in WorkZone Content Server FESD Web Services database, 'false' in method input and output = 'N' in WorkZone Content Server FESD Web Services database.
organizationName	Name	name1	
CVRnumberIdentifier	Name	name_code	For input: Only applicable for CreateOrganization method;

FESD Parameter	WorkZone Content Server FESD Web Services Table	WorkZone Content Server FESD Web Services Field	WorkZone Content Server FESD Web Services Implementation Notes
			ignored for UpdateOrganization .
businessActivity	Contact_info	info	Contact_info.custom_label field is filled in with 'Branche'.
companyType	Name	company_type	Parameter type is char(32) instead of int(3) specified by FESD standard.
organizationStartDate	Name	start_date	
organizationEndDate	Name	end_date	
situationAddress	See Organization Address.		
mailDeliveryAddress	See Organization Address.		
roleRelation			Currently not supported by OpenWSI.

Organization Address

Addresses are related to their Organizations via **name_key** fields in the **Name** and **Name_address** tables.

Implementation is the same as for Person Address.

Organization Role Relation

Organization Role Relations are currently not supported by OpenWSI.

OrganizationalUnit

Mapping of the FESD attributes to the WorkZone Content Server FESD Web Services database fields and notes on WorkZone Content Server FESD Web Services implementation are presented in the table below.

FESD Parameter	WorkZone Content Server FESD Web Services Table	WorkZone Content Server FESD Web Services Field	WorkZone Content Server FESD Web Services Implementation Notes
userIdentifier	N/A	N/A	Is recorded to Use_log.identification field.
organizationalUnitIdentifier	Name	fesd_id_key	Parameter type is GUID.
uniqueIdentifier	Name	fesd_id_key	Parameter type is GUID instead of int(10) specified by FESD standard.
N/A	Name	name_type	Is filled in with 'V' value.
CVRnumberIdentifier	N/A	N/A	Ignored at input.
advertisementProtectionIndication	Name	advertisement	'true' in method input and output = 'J' in WorkZone Content Server FESD Web Services database, 'false' in method input and output = 'N' in WorkZone Content Server FESD Web Services database.
organizationalUnitName	Name	name1	
productionUnitIdentifier	Name	name_code	For input: Only applicable for CreateOrganizationalUnit method; ignored for UpdateOr-

FESD Parameter	WorkZone Content Server FESD Web Services Table	WorkZone Content Server FESD Web Services Field	WorkZone Content Server FESD Web Services Implementation Notes
			ganizationalUnit.
businessActivity	Contact_ info	info	First row in subtable Contact_ info . Field custom_label is filled in with 'Branche' (=Trade) value; field priority is filled in with '1'.
businessSubActivity	Contact_ info	info	Second row in subtable Contact_ info . Field custom_label is filled in with 'Branche' (=Trade) value; field priority is filled in with '2'.
unitStartDate	Name	start_date	
unitEndDate	Name	end_date	
situationAddress	See OrganisationalUnit Address.		
mailDeliveryAddress	See OrganisationalUnit Address.		
roleRelation			Currently not supported by OpenWSI.
legalUnit	Contact_ info	info	Not implemented by OpenWSI.
productionUnit	Contact_ info	info	Not implemented by OpenWSI.

OrganisationalUnit Address

Addresses are related to their Organizational Units via **name_key** fields in **Name** and **Name_address** tables.

Implementation is the same as for Person Address.

OrganizationalUnit Role Relation

Organizational Unit Role Relations are currently not supported by OpenWSI.

Building

Mapping of the FESD attributes to the WorkZone Content Server FESD Web Services database fields and notes on WorkZone Content Server FESD Web Services implementation are presented in the table below.

FESD Parameter	WorkZone Content Server FESD Web Services Table	WorkZone Content Server FESD Web Services Field	WorkZone Content Server FESD Web Services Implementation Notes
userIdentifier	N/A	N/A	Is recorded to the Use_log.identification field.
buildingIdentifier	Name	fesd_id_key	Mandatory parameter of type GUID instead of optional parameter specified by FESD standard.
buildingNumber	Contact_info	info	Field custom_label contains value "bygningsNr" - house number.
municipalRealPropertyIdentifier	Name	name_code	Is retrieved from WorkZone Content Server FESD Web Services database by the following algorithm: <ol style="list-style-type: none"> 1. Retrieve name_key from a row found in Name table by fesd_id_key = buildingIdentifier. 2. Retrieve name_ref_key from a

FESD Parameter	WorkZone Content Server FESD Web Services Table	WorkZone Content Server FESD Web Services Field	WorkZone Content Server FESD Web Services Imple- mentation Notes
----------------	--	--	--

row found in **Name_name** table by **name_key** and **name_type = "1"** ("Real property").

- Retrieve **name_code** from a row found in **Name** table by **name_key = name_ref_key**.

municipalityCode	Name	name_code	Is retrieved from WorkZone Content Server FESD Web Services database by the following algorithm:
			<ol style="list-style-type: none"> Retrieve Name_ref_key from a row found in Name_name table by name_key = name_key of found Real Property. Retrieve name_code from a row

FESD Parameter	WorkZone Content Server FESD Web Services Table	WorkZone Content Server FESD Web Services Field	WorkZone Content Server FESD Web Services Implementation Notes
----------------	---	---	--

found in the **Name** table by **name_key = name_ref_key**.

BBRIdentifier	Name	name_code	Is retrieved from the original record in the Name table.
address	See Building Address.		

Building Address

Addresses are related to Buildings via **name_key** fields in **Name** and **Name_address** tables.

Implementation is the same as for Person Address.

Cadastre

Only search by `cadastreIdentifier` is currently supported.

Mapping of the FESD attributes to the WorkZone Content Server FESD Web Services database fields and notes on WorkZone Content Server FESD Web Services implementation are presented in the table below.

FESD Parameter	WorkZone Content Server FESD Web Services Table	WorkZone Content Server FESD Web Services Field	WorkZone Content Server FESD Web Services Implementation Notes
<code>userIdentifier</code>	N/A	N/A	Is recorded to the <code>User_log.identification</code> field.
<code>cadastreIdentifier</code>	Name	<code>fesd_id_key</code>	Parameter type is GUID.
<code>cadastralDistrictIdentifier</code>	Name	<code>name_code</code>	Is retrieved from the WorkZone Content Server FESD Web Services database by the following algorithm: <ol style="list-style-type: none"> 1. Retrieve <code>name_key</code> from a row found in Name table by <code>fesd_id_key = cadastreIdentifier</code>. 2. Retrieve <code>shareholders_key</code> from a row found in Cadastre table by <code>name_key</code>.

FESD Parameter	WorkZone Content Server FESD Web Services Table	WorkZone Content Server FESD Web Services Field	WorkZone Content Server FESD Web Services Implementation Notes
----------------	---	---	--

3. Retrieve name_code from a row found in Name table by name_key = shareholders_key.

municipalityCode	Name	name_code	<p>Is retrieved from the WorkZone Content Server FESD Web Services database by the following algorithm:</p> <ol style="list-style-type: none"> 1. Retrieve name_key from a row found in Name table by fesd_id_key = cadastreidentifier. 2. Retrieve municipality_key from a row found in Cadastre table by name_key. 3. Retrieve name_code from a row found in Name
------------------	------	-----------	--

FESD Parameter	WorkZone Content Server FESD Web Services Table	WorkZone Content Server FESD Web Services Field	WorkZone Content Server FESD Web Services Imple- mentation Notes
----------------	--	--	--

table by **name_**
key = muni-
city_key.

landParcelMunicipalPartNumber	Contact_info	info	Field custom_label contains value "delNr".
landParcelIdentifier	Cadastre	cadastre_no	Is retrieved from WorkZone Content Server FESD Web Services database by the following algorithm: <ul style="list-style-type: none"> 1. Retrieve name_ key from a row found in Name table by fesd_id_ key = cadastreiden- tifier. 2. Retrieve cadastre_no from a row found in Cadastre table by name_key.
realPropertyIdentifier	Name	name_code	Is retrieved from WorkZone Content Server FESD Web Services database by the following algorithm:

FESD Parameter	WorkZone Content Server FESD Web Services Table	WorkZone Content Server FESD Web Services Field	WorkZone Content Server FESD Web Services Imple- mentation Notes
----------------	--	--	--

1. Retrieve **name_key** from a row found in **Name** table by **fesd_id_key = build-
ingIdentifier**.
2. Retrieve **name_ref_key** from a row found in **Name_name** table by **name_key** and **name_type = "1"** ("Real property").
3. Retrieve **name_code** from a row found in **Name** table by **name_key = name_ref_key**.

RealProperty

Currently the method returns only a list of Building identifiers for the requested Real Property.

Mapping of the FESD attributes to the WorkZone Content Server FESD Web Services database fields and notes on WorkZone Content Server FESD Web Services implementation are presented in the table below.

FESD Parameter	WorkZone Content Server FESD Web Services Table	WorkZone Content Server FESD Web Services Implementation Notes	WorkZone Content Server FESD Web Services Implementation Notes
userIdentifier	N/A	N/A	Is recorded to the Use_log.identification field.
realPropertyIdentifier	Name	fesd_id_key	Parameter type is GUID.
landParcelIdentifier	Cadastre	cadastre_no	Is retrieved from the WorkZone Content Server FESD Web Services database by the following algorithm: <ol style="list-style-type: none"> 1. Retrieve name_key from a row found in Name table by fesd_id_key = realPropertyIdentifier. 2. Retrieve name_key from a row found in Name_name

FESD Parameter	WorkZone Content Server FESD Web Services Table	WorkZone Content Server FESD Web Services Implementation Notes	WorkZone Content Server FESD Web Services Implementation Notes
----------------	---	--	--

table by **name_ref_key = name_key** and **name_type = "1"** ("Real property").

3. Retrieve **cadastre_no** from a row found in **Cadastre** table by **name_key**.

cadastralDistrictIdentifier	Name	name_code	<p>Is retrieved from the WorkZone Content Server FESD Web Services database by the following algorithm:</p> <ol style="list-style-type: none"> 1. Retrieve name_key from a row found in Name table by fesd_id_key = realPropertyIdentifier. 2. Retrieve name_
-----------------------------	------	-----------	---

FESD Parameter	WorkZone Content Server FESD Web Services Table	WorkZone Content Server FESD Web Services Implementation Notes	WorkZone Content Server FESD Web Services Implementation Notes
----------------	---	--	--

key from a row found in **Name_name** table by **name_ref_key = name_key** and **name_type = "1"** ("Real property").

3. Retrieve **shareholders_key** from a row found in **Cadastre** table by **name_key**.
4. Retrieve **name_code** from a row found in **Name** table by **name_key = shareholders_key**.

municipalityCode	Name	name_code	Is retrieved from the WorkZone Content Server FESD Web Services database by the following algorithm:
------------------	------	-----------	--

FESD Parameter	WorkZone Content Server FESD Web Services Table	WorkZone Content Server FESD Web Services Implementation Notes	WorkZone Content Server FESD Web Services Implementation Notes
----------------	---	--	--

1. Retrieve **name_key** from a row found in **Name** table by **fesd_id_key = realPropertyIdentifier**.
2. Retrieve **name_key** from a row found in **Name_name** table by **name_ref_key = name_key** and **name_type = "1"** ("Real property").
3. Retrieve **municipality_key** from a row found in **Cadastre** table by **name_key**.
4. Retrieve **name_code** from a row found in **Name** table by **name_key = municipality_key**.

FESD Parameter	WorkZone Content Server FESD Web Services Table	WorkZone Content Server FESD Web Services Implementation Notes	WorkZone Content Server FESD Web Services Implementation Notes
----------------	---	--	--

landParcelMunicipalPartNumber	Contact_info	info	Is retrieved from the WorkZone Content Server FESD Web Services database by the following algorithm:
-------------------------------	--------------	------	--

1. Retrieve **name_key** from a row found in **Name** table by `fedd_id_key = realPropertyIdentifier`.
2. Retrieve `name_key` from a row found in `Name_name` table by `name_ref_key = name_key` and `name_type = "1"` ("Real property").
3. Retrieve `info` from a row found in `Contact_info` table by `name_key` and `custom_label = 'delNr'`.

FESD Parameter	WorkZone Content Server FESD Web Services Table	WorkZone Content Server FESD Web Services Implementation Notes	WorkZone Content Server FESD Web Services Implementation Notes
buildingIdentifier	N/A	N/A	<p>Is retrieved from the WorkZone Content Server FESD Web Services database by the following algorithm:</p> <ol style="list-style-type: none"> 1. Retrieve name_key from a row found in Name table by fedd_id_key = realPropertyIdentifier. 2. Retrieve name_key from all rows in Name_name table found by name_ref_key = name_key and name_type = "1" ("Real property"). 3. For each row retrieve fedd_id_key from a row found in Name table by name_key.

FESD Parameter	WorkZone Content Server FESD Web Services Table	WorkZone Content Server FESD Web Services Implementation Notes	WorkZone Content Server FESD Web Services Implementation Notes
cadastralIdentifier	N/A	N/A	<p>Is retrieved from the WorkZone Content Server FESD Web Services database by the following algorithm:</p> <ol style="list-style-type: none"> 1. Retrieve name_key from a row found in Name table by fedd_id_key = realPropertyIdentifier. 2. Retrieve name_key from a row found in Name_name table by name_ref_key = name_key and name_type = "1" ("Real property"). 3. Retrieve fedd_id_key from a row found in Name table by name_key.

CaseFile

Mapping of the FESD attributes to the WorkZone Content Server FESD Web Services database fields and notes on WorkZone Content Server FESD Web Services implementation are presented in the table below.

FESD Parameter	WorkZone Content Server FESD Web Services Table	WorkZone Content Server FESD Web Services Field	WorkZone Content Server FESD Web Services Implementation Notes
userIdentifier	N/A	N/A	Is recorded to Use_log.identification field.
caseFileIdentifier	File	fed_id_key	Parameter type is GUID instead of int (10) specified by FESD standard.
uniqueIdentifier	File	fed_id_key	Parameter type is GUID instead of int (10) specified by FESD standard.
caseFileNumber	File	file_no	
caseFileNumberIdentifier	File	file_no	
fileClass	File	file_class	Obsolete. This parameter was added by KMD because file.file_class field was mandatory in Captia and did not contain default values. The field was intended to classify CaseFiles in Captia.
year	File	year	Currently not supported by OpenWSI.

FESD Parameter	WorkZone Content Server FESD Web Services Table	WorkZone Content Server FESD Web Services Field	WorkZone Content Server FESD Web Services Implementation Notes
sequenceNumber	File	file_key	
paperIndicator	File	medium	Parameter type is unsignedByte instead of char(1) specified by FESD standard. Method accepts only '0' and '1'.
creationDate	File	created	
titleText	File_title	text	
titleNonDisclosureIndicator	File	not_public_title	Parameter type is unsignedByte instead of char(1) specified by FESD standard. Method accepts only '0' and '1'. '1' in method input and output = 'J' in WorkZone Content Server FESD Web Services database, '0' in method input and output = 'N' in WorkZone Content Server FESD Web Services database.
titleNonDisclosureText	File	public_title	
caseFileStatusCode	File	state	Parameter type is char(32) instead of char(2) specified by FESD standard.
caseFileTypeCode	File	file_type	Parameter type is char(32) instead of char(10) specified by FESD standard.

FESD Parameter	WorkZone Content Server FESD Web Services Table	WorkZone Content Server FESD Web Services Field	WorkZone Content Server FESD Web Services Implementation Notes
case-FileResponsibleOfficerReference	File	officer	<p>Parameter type is GUID instead of int (10) specified by FESD standard.</p> <p>The parameter is stored in WorkZone Content Server FESD Web Services database by the following algorithm:</p> <ol style="list-style-type: none"> 1. Retrieve name_key from a row found in Name table by fesd_id_key = incoming GUID. 2. Retrieve name_code from a row found in Employee table by name_key = found name_key 3. Retrieved value is used for storing into the field. The reversed algorithm is used for retrieving a value from the field.
nonDis-closureDescriptionText	File	legis-lation_ref	
latestRecordDate	N/A	N/A	Currently not supported by OpenWSI. Ignored at input.

FESD Parameter	WorkZone Content Server FESD Web Services Table	WorkZone Content Server FESD Web Services Field	WorkZone Content Server FESD Web Services Implementation Notes
retentionTime	File	retention	
disposalCode	File	disposal_code	Parameter type is char(32) instead of char(2) specified by FESD standard.
disposalDate	File	disposal	
precedensText	File	precedent	
precedensReference	N/A	N/A	Not implemented by OpenWSI. Ignored at input.
loanDate	File_location	date_received	
borrowerReference	File_location	name_code	Parameter type is GUID instead of int (10) specified by FESD standard. Algorithms of storing and fetching this parameter to / from WorkZone Content Server FESD Web Services database are similar to algorithms for <code>case-FileResponsibleOfficerReference</code> parameter of <code>CaseFile</code> .
numberHistoricIdentifier	File	previous_no	

FESD Parameter	WorkZone Content Server FESD Web Services Table	WorkZone Content Server FESD Web Services Field	WorkZone Content Server FESD Web Services Implementation Notes
createdByReference	File	create_user	Parameter type is GUID instead of int (10) specified by FESD standard. For output, it is retrieved as <code>fesd_id_key</code> from a row found in Users table by <code>user_name = value of the field</code> .
latestUpdateByReference	File	update_user	Parameter type is GUID instead of date specified by FESD standard. For output, it is retrieved as <code>fesd_id_key</code> from a row found in Users table by <code>user_name = value of the field</code> .
lastUpdateDate	File	updated	Parameter type is date instead of int (10) specified by FESD standard.
comment	See CaseFile Comment.		
reminder	See CaseFile Reminder.		
caseFilePartyReference	See CaseFile Party.		
caseFileObjectReference, caseFileObjectName	See CaseFile Object.		
caseFileParty	File_name	fesd_id_key	Parameter type is GUID instead of int (10) specified by FESD standard. Each Party is stored as a separate row in the File_name table.

FESD Parameter	WorkZone Content Server FESD Web Services Table	WorkZone Content Server FESD Web Services Field	WorkZone Content Server FESD Web Services Implementation Notes
caseFileObject	File_name	fed_id_key	Parameter type is GUID instead of int (10) specified by FESD standard. Each Object is stored as a separate row in the File_name table.

CaseFile Comment

Comments are related to their CaseFiles via **file_key** fields in **File** and **File_comment** tables. Mapping of the FESD attributes to the WorkZone Content Server FESD Web Services database fields and notes on WorkZone Content Server FESD Web Services implementation are presented in the table below.

FESD Parameter	WorkZone Content Server FESD Web Services Table	WorkZone Content Server FESD Web Services Field	WorkZone Content Server FESD Web Services Implementation Notes
informationTypeCode	File_comment	comment_type	Parameter type is char(32) instead of char(2) specified by FESD standard.
cancellationDate	File_comment	delete_date	
createdOnBehalfOfReference	File_comment	on_behalf_of	Parameter type is GUID instead of int (10) specified by FESD standard. Algorithms of storing and fetching this

FESD Parameter	WorkZone Content Server FESD Web Services Table	WorkZone Content Server FESD Web Services Field	WorkZone Content Server FESD Web Services Implementation Notes
----------------	---	---	--

parameter to / from WorkZone Content Server FESD Web Services database are similar to algorithms for **case-FileResponsibleOfficerReference** parameter of CaseFile.

commentText	File_com-	text ment	
commentDocumentReference	File_com-	vattach_ record_ key	Parameter type is GUID instead of int (10) specified by FESD standard.

CaseFile Reminder

Reminders are related to their CaseFiles via **file_key** fields in **File** and **Reminder** tables.

Mapping of the FESD attributes to the WorkZone Content Server FESD Web Services database fields and notes on WorkZone Content Server FESD Web Services implementation are presented in the table below.

FESD Parameter	WorkZone Content Server FESD Web Services Table	WorkZone Content Server FESD Web Services Field	WorkZone Content Server FESD Web Services Implementation Notes
----------------	---	---	--

reminderDate	Reminder	reminder_ date	
--------------	----------	----------------	--

FESD Parameter	WorkZone Content Server FESD Web Services Table	WorkZone Content Server FESD Web Services Field	WorkZone Content Server FESD Web Services Implementation Notes
reminderTypeCode	Reminder	reminder_code	Parameter type is char(3) instead of char(2) specified by FESD standard.
descriptionText	Reminder	text	
responsibleReference	Reminder	name_code	Parameter type is GUID instead of int(10) specified by FESD standard. Algorithms of storing and fetching this parameter to / from WorkZone Content Server FESD Web Services database are similar to algorithms for caseFileResponsibleOfficerReference parameter of CaseFile.
N/A	Reminder	name_key	Is filled in with name_key of Employee referred by name_code .
N/A	Reminder	name_type	Is filled in with 'M' (Employee)

CaseFile Party

Parties are related to their CaseFiles via **file_key** and **name_key** fields in **File_name** table.

Mapping of the FESD attributes to the WorkZone Content Server FESD Web Services database fields and notes on WorkZone Content Server FESD Web Services implementation are presented in the table below.

FESD Parameter	WorkZone Content Server FESD Web Services Table	WorkZone Content Server FESD Web Services Field	WorkZone Content Server FESD Web Services Implementation Notes
N/A	File_name	file_key	Is filled in with file_key of the corresponding row from main File table.

FESD Parameter	WorkZone Content Server FESD Web Services Table	WorkZone Content Server FESD Web Services Field	WorkZone Content Server FESD Web Services Implementation Notes
N/A	File_name	custom_label	Is filled in with the "Sagspart" value.
N/A	File_name	name_key	Is filled in with the value found in Name table by fesd_id_key = value of Party's GUID from method's input.
N/A	File_name	name_code	Is filled in with name_code of Employee referred by name_key .
N/A	File_name	name_type	Is filled in with name_type of Employee referred by name_key .

CaseFile Object

Objects are related to their CaseFiles via **file_key** and **name_key** fields in **File_name** table. Mapping of the FESD attributes to the WorkZone Content Server FESD Web Services database fields and notes on WorkZone Content Server FESD Web Services implementation are presented in the table below.

FESD Parameter	WorkZone Content Server FESD Web Services Table	WorkZone Content Server FESD Web Services Field	WorkZone Content Server FESD Web Services Implementation Notes
N/A	File_name	file_key	Is filled in with file_key of the corresponding row from main File table.
N/A	File_name	custom_label	Is filled in with the "Sagsobject" value.
N/A	File_name	name_key	Is filled in with the value found in Name table found by fesd_id_key = value of Party's GUID from method's input.
N/A	File_name	name_code	Is filled in with name_code of Employee referred by name_key .

FESD Parameter	WorkZone Content Server FESD Web Services Table	WorkZone Content Server FESD Web Services Field	WorkZone Content Server FESD Web Services Implementation Notes
N/A	File_name	name_type	Is filled in with name_type of Employee referred by name_key .

Terms and conditions

Intellectual Property Rights

This document is the property of KMD. The data contained herein, in whole or in part, may not be duplicated, used or disclosed outside the recipient for any purpose other than to conduct business and technical evaluation provided that this is approved by KMD according to the agreement between KMD and the recipient. This restriction does not limit the recipient's right to use information contained in the data if it is obtained from another source without restriction set out in the agreement between KMD and the recipient or by law.

Disclaimer

This document is intended for informational purposes only. Any information herein is believed to be reliable. However, KMD assumes no responsibility for the accuracy of the information. KMD reserves the right to change the document and the products described without notice. KMD and the authors disclaim any and all liabilities.

Copyright © KMD A/S 2021. All rights reserved.